



Data Sheet

Beacon® LED Header System



General Description: The Beacon® LED Header from Stylmark is a versatile signage solution. It can be used as directional signage, nestled into shelving/gondola system to highlight a signature brand or incorporated into commercial environment setting conveying information.

As retail and commercial environments become more complicated, consumers need visual cues to help guide them through a store or to a particular display. The Beacon™ from Stylmark will enhance the overall shopping experience.

Performance Specifications:

Chromaticity:

- Warm white:** □ 2500K - 2800K
- Neutral White:** □ 3000K – 3300K
- Cool White:** □ 4000K – 4300K (standard)
- Daylight White:** □ 6000K – 6500K

CRI: 80

Luminance: 300 lumen/ft (typical)
18 LED/ft

Lamp Life: 70% lumen maintenance after 50,000 hours of continuous power on.

Power Consumption¹: 3.2 W/ft

Construction Specifications:

Materials: Anodized Aluminum, Acrylic or Stainless Steel options available
Note: Acrylic toppers have the option to be alternate colors i.e. black letters on white, red acrylic with white letters, etc.

Length Sizes:
Track: 36", 54", or 72"
Sign Holder: Varying lengths available
Topper: (L) 42" x (W) 1.5" x (H) 5.75"

Finishes: see Stylmark Color Library

Environmental Specifications:

Protection Rating: For indoor use only

The Beacon Header LED fixture is fabricated to match custom dimensions. As the Header also includes mounting components, the LED light assembly length will be less than the length of the Header. Stylmark will configure the LED light assembly length to optimize the available space using Stylmark's LED light engine modules. Please consult Stylmark for information specific to your order.

In order to continually improve our products, Stylmark reserves the right to make changes to specifications or materials without prior notice.

UL Listed or Recognized Components

¹ LED UL Listed Class 2, 24 Vdc constant voltage power supply/driver required, provided by Stylmark