

Mirror Solutions by **stylmark*** TILT

Data Sheet

General Description: Mirror *Solutions* by Stylmark come fully glazed and ready to install. Available in standard single pane sizes, with or without LED lighting, these mirrors expand the visual space of any room while providing elegant functionality. Use the included bracket to install as a leaning mirror to the wall. The LED-lit TILT Mirror plugs into a standard wall outlet.

Applications: Retail fitting rooms, restrooms, spas, salons and hotel guest suites

Construction Specifications:

Frame Material: Anodized aluminum
Frame Finish: See Stylmark Color Library

Mirror: ¼" clear mirror with pencil ground edges and

Category 1 safety backing.

Mount Bracket Material: 16 Ga Galvanneal Steel

Mounting Surface: Mechanically sound surface with fasteners (obtain

locally) rated to 75 lbs pullout

Lighting Specifications (back-lit models):

Source: LED **Nominal Length:** 60" or 72"

 Nominal Wattage:
 32.5W or 39W (@24Vdc)

 Average Rated Life:
 50,000 hours (L70)

 Color Temperature:
 3000K, 3700K, 4200K

Color Rendering Index: 85

Illuminance¹: 28'' wide = 57 f.c., 36'' wide = 44 f.c.

Power Requirements: 120~240 VAC, 50~60 HZ, 1.8 A max.

Includes 3-prong plug (NEMA 5-15 type) Electrical connection behind mirror is required

¹ Measurements taken from horizontal center of mirror pane at vertical center height



ETL Listed Tested to UL Standard 962 and CSA C22.2 No. 250.0-08

MIRRKT

In order to continually improve our products, Stylmark reserves the right to make changes to specifications or materials without prior notice.

Identification:

Model	Description	Mirror Size (O.D.)
620091-01	TILT: Single Pane Mirror with	28" x 60" (29" x 61")
620091-02	mounting hardware	28" x 72" (29" x 73")
620091-03		36" x 72" (37" x 73")
620092-01	TILT: LED-lit, Single Pane Mirror	28" x 60" (28-1/4" x 60-1/4")
620092-02	with mounting hardware	28" x 72" (28-¼" x 72-¼")
620092-03		36" x 72" (36-¼" x 72-¼")

